

Ontario Federation of Snowmobile Clubs SIGN GUIDE

Side A

Effective Oct. 15, 2003

GENERAL SIGN INSTRUCTIONS

- Regulatory and Cautionary Signs take precedent over other signs
- NO sign shall interfere with the sight lines of Cautionary & Regulatory signs
- Signs 1.25m to 2m ABOVE ground 1m to 1.5m to RIGHT of Trail
- Signs are to be mounted ONE per Post NO signs mounted on the REVERSE side
- Trees or other natural locations to be used ONLY when a post is NOT an option and location is CLEARLY visible to the trail
- OFSC Sign Standards apply unless regulated by Law

1m to 1.5m

SIGN HEIGHT & PLACEMENT

12" X 12" REFLECTIVE SIGNS

TRAIL

DIRECTION ARROW

Note: drawings are simulated and not to scale

USE TO MARK THE ENTRANCE 1m to 1.5m TO A CURVE WHERE ADDITIONAL GUIDANCE IS REQUIRED. ONLY ONE SIGN SHALL BE USED. MOUNTED IN A HORIZONTAL POSITION to 120m (as shown) AT A LOCATION VISIBLE TO THE APPROACHING OPERATOR. INSTALL A SLOW SIGN 100m TO 120m BEFORE ARROW SIGN. Chrevrons shall be removed by Oct. 15, 2004. Trail SLOW

CAUTION & REGULATORY SIGNS



STOP



STOP AHEAD



SLOW



DIRECTION ARROW



ICE CROSSING



RAILROAD CROSSING





BRIDGE HAZARD MARKERS LEFT RIGHT



MAXIMUM 50 km/h



TRAIL ENDS

TRAIL CLOSED



USE AT YOUR OWN RISK SIGN





PONTARIO PRESCRIBED TRAIL **PRESCRIBED**

TRAIL

Set back from trail in fields with two rows of stakes

Trail

0.5m to 1.5m

Trail

11111

1m to 1.5

RAILROAD **CROSSING SIGNS** A STOP SIGN WILL BE PLACED 5 TO 10m PRIOR TO THE RAILROAD CROSSING. RAILROAD CROSSING SIGN TO BE INSTALLED 100 TO 120M PRIOR TO RAILROAD CROSSING. NO SIGNS BETWEEN THE CROSSING SIGN AND THE STOP SIGN IF LESS THAN 120m BETWEEN TWO RAILWAY


ICE CROSSING SIGNS

CROSSINGS, A SECOND CROSSING SIGN

IS NOT NEEDED IF UNOBSTRUCTED

VIEW BETWEEN THE TWO CROSSINGS.

USE 5m to 10m PRIOR TO ICE SURFACE. INSTALL A SLOW SIGN 100m to 120m BEFORE ICE CROSSING SIGN. (Per approved standards)



ORANGE (Tremdad Real Orange or Equivalent) 35mm in dia.(1.25") minimum 1.25m to 2m in height 35mm sq WHITE REFLECTOR(1sq. ") (min.) PLACE APPOX. 6cm (2") DOWN FROM THE TOP ON TWO SIDES FACING TRAIL, (Min.) USE MINIMUM - SINGLE ROW - TO DIVIDE A LAKE TRAIL, USE MINIMUM DOUBLE ROW TO MARK A FIELD TRAIL. INSTALL TRAIL ENDS SIGN WHEN TRAIL TERMINATES AT NON-STAKED LAKE. Conform by Oct. 15, 2004.

Note: drawings are simulated and not to scale